

# iPlug

**1:1** 600-800 VA



USB plug



GS Nemko certified



Plug & Play installation

## HIGHLIGHTS

- **Compact**
- **Versatile**
- **Robust**
- **Contemporary design**
- **Auto restart**
- **Battery swap**

The iPlug series is the ideal solution for protecting household and small office systems. Its compact size and versatility (push-button operation, LED status panel and user replaceable batteries), make iPlug easy to install within a domestic environment to protect systems from surges and blackouts.

When the mains fails, the load is powered from a pseudo-sine wave inverter, to provide sufficient runtime for computer system shutdown using PowerShield<sup>3</sup> software,

which can be downloaded free from [www.riello-ups.com](http://www.riello-ups.com)

### Versatile, robust and contemporary design

The iPlug's compact and ergonomic design allow it to be easily installed in professional and domestic environments.

iPlug is extremely versatile and its innovative cable management feature ensures a tidy, easy to manage installation.

## Advanced communications

PowerShield<sup>3</sup> software allows for the safe shutdown of connected IT systems on mains power supply failure. PowerShield<sup>3</sup> provides efficient and intuitive UPS management using bar chart displays for important operating information.

## Auto restart

The UPS automatically restarts upon the restoration of mains power after having shut down once the batteries have run out following a black out (Auto restart).

## Environmental protection ECO Line

With energy savings in mind, the iPlug range features a shut-off button to reduce energy consumption during periods of prolonged inactivity.

## Applications

LCD monitors, personal computers, video terminals, printers, scanners and fax machines.

## Features

- Compact and ergonomic
- 5 sockets protected against black-outs
- 3 sockets protected against overvoltage for the supply of loads with larger absorption loads e.g laser printers
- Ability to switch on the UPS without a mains power supply (Cold Start)
- User replaceable batteries (Battery Swap)
- USB interface
- Floor-standing or desktop installation
- Power-supply cable included
- Built-in short circuit protection
- Auto restart (when mains power is restored, after discharge of the batteries)
- GS/Nemko safety seal

- Available with French (2P+T), British, Schuko and Italian outlets.
- PowerShield<sup>3</sup> supervision and shutdown software for Windows operating systems 8, 7, 2008, Vista, 2003, XP, Linux, Mac OS X and Sun Solaris
- Plug and play function.

## 2-YEAR WARRANTY

## CONFIGURATOR FOR MODEL SELECTION

Load type	VA power rating *
Personal computers	250
LCD Monitors	70
Scanners, printers	200
Modems, TVs, DVD players, PlayStations, Hi-Fi systems, telephones, Faxes	50
Laser printers **	200

\* Estimated average value.

\*\* iPlug filtered output power supply is recommended.

## AVAILABLE SOCKETS



SCHUKO  
SOCKET  
CEE 7/7P



FRENCH  
SOCKET  
CEE 7/5



ITALIAN  
SOCKET  
CEI 23/16



BRITISH  
SOCKET  
BS1363A


## AVAILABLE OPTIONS

### SOFTWARE

PowerShield<sup>3</sup>

## DETAILS


FILTERED SOCKETS: PROTECTED  
AGAINST OVERVOLTAGE ONLY



SOCKETS WITH UPS PROTECTION  
(NO BREAK IN POWER IF MAINS FAILS)

IEC SOCKETS WITH UPS PROTECTION

USB COMMUNICATION PORT



SAFETY FUSE



MODELS	IPG 600	IPG 800
<b>POWER</b>	<b>600 VA/360 W</b>	<b>800 VA/480 W</b>
<b>INPUT</b>		
Nominal voltage	220-240 Vac	
Input voltage tolerance frequency	230 Vac (+20/-25%)	
Frequency	50/60 Hz with automatic selection	
<b>OUTPUT</b>		
Voltage during mains operation	230 Vac (+20/-25%)	
Voltage during battery operation	230 Vac (+/- 10%)	
Frequency during battery operation	50 or 60 Hz (+/- 1%)	
Waveform	Pseudo Sinusoidal	
<b>BATTERIES</b>		
Type	VRLA AGM maintenance-free lead based	
Recharge time	6-8 hours	
<b>OTHER FEATURES</b>		
Net weight (kg)	3.7	4.1
Gross weight (kg)	4	4.4
Dimensions (WxDxH) (mm)	185 x 313 x 99	
Packaging dimensions (WxDxH) (mm)	260 x 380 x 140	
Protections	Excessive low battery - overvoltage - short circuit	
Communications	USB	
Output sockets	6 sockets (Schuko or Italian or French or British) + 2 IEC 320 C13	
Standards	EN 62040-1-1 and Directive 2006/95/EC; EN 62040-3 EN 62040-2 and Directive 2004/108 EC	
Certificates	CE; GS/NEMKO on Schuko version	
Operating temperature	0 °C / +40 °C	
Colour	Black	
Altitude and relative humidity	6000 m max altitude, < 95% non-condensing	
Equipment provided	power cable, user guide	

[www.ups-riello.com](http://www.ups-riello.com)

**RPS S.p.A.**

**LEGNAGO (VR)**  
**Registered office**  
Viale Europa, 7 ZA1  
37045 LEGNAGO (Verona)  
Tel +39 0442 635811  
Fax +39 0442 629098  
www.riello-ups.com  
riello@riello-ups.com

**CORMANO (MI)**  
**Sales Office**  
Via Somalia, 20  
20032 CORMANO (Milano)  
Tel +39 02 663271  
Fax +39 02 66327351

**ROME**  
**Sales Office**  
Via Fosso della Magliana, 34/G  
00148 ROME  
Tel +39 06 65192125  
Fax +39 06 65192247



**PRE-SALES SUPPORT**  
(TEC)  
tec@riello-ups.com



**AFTER-SALES SUPPORT**  
(UPService)  
service@riello-ups.com

**RIELLO UPS Ltd. (UK)**  
Unit 50 Clywedog Road North  
Wrexham Industrial Estate  
Wrexham LL13 9XN  
Tel +44 (0)800 269 394  
Fax +44 (0)1978 729 290

**CONSTANT POWER SERVICES Ltd. (UK)**  
Unit 3 - Trust Industrial Estate,  
Wilbury Way - Hitchin, Herts, SG4 0UZ  
Tel +44 (0)1462 422 955  
Fax +44 (0)1462 422 754

**RIELLO UPS GmbH (DEUTSCHLAND)**  
Siemensstraße 12  
21465 Reinbek bei Hamburg  
Tel +49 (0)40 727 57-06  
Fax +49 (0)40 727 57-189

**AROS GmbH (DEUTSCHLAND)**  
Neufahrner Str. 12b  
D-85375 Neufahrn/Grünbeck  
Tel +49 8165 / 9458-0  
Fax +49 8165 / 9458-26

**RIELLO ENERDATA s.l.u. (ESPAÑA)**  
C/ Labradores, 13 Parque Empresarial  
Prado del Espino  
28660 Boadilla del Monte - Madrid  
Tel +34 916 333 000  
Fax +34 916 321 793

**Delegación Andalucía**  
C/ Aviación 18, P. I. Calonge,  
Edificio Morera y Vallejo 1, 1ª Planta  
41007 Sevilla  
Tel +34 955 040 044  
Fax +34 955 040 041

**RIELLO TDL s.l. (ESPAÑA)**  
C/Berguedà, 6 bis  
Pol. Ind. Plà de la Bruguera  
08211 Castellar del Vallès, Barcelona  
Tel +34 (0)93 74 71 210  
Fax +34 (0)93 71 46 562

**RIELLO ONDULEURS S.a.r.l. (FRANCE)**  
2/4 Rue du Bois Chaland,  
ZAC du Bois Chaland - 91090 Lisses  
Tel +33 (0)1 60 875454  
Fax +33 (0)1 60 875450

**Agence Rhone Alpes - Sud**  
147 Avenue M. Mérieux,  
Parc de Sacuny, Park Avenir 1  
69530 Brignais  
Tel +33 (0)4 72 177108  
Fax +33 (0)4 78 351422

**RIELLO PCI India Pvt. Ltd. (INDIA)**  
Prime Group Building,  
11/5B, Pusa Road, New Delhi - 110 005  
Tel +91 11 41 888 999 (30 lines),  
Tel +91 11 41 888 888  
Fax +91 11 2575 5815

**Riello UPS (Asia) Co., Ltd.**  
**(PEOPLE'S REPUBLIC OF CHINA)**  
28F, 500, Fute Dong Er Road,  
Waigaoqiao Free Trade Zone,  
Pudong District - 200131 Shanghai  
Tel +86 21 50464748  
Fax +86 21 50464648

**Sales office Beijing**  
No.418, 4F, Block A, Gaode Plaza, 10  
Huayuan Dong Road,  
Haidian District - Beijing  
Tel +86 10 82038861 / 8862  
Fax +86 10 82038863

**Sales office Guangzhou**  
Address Unit 1507 East Building,  
Dongshan Square, No. 65,  
Xianlie Zhong Road, Yuxiu District  
510095, Guangzhou  
Tel +86 20 28848001  
Fax +86 20 28848002

**Singapore Rep. office (ASIA PACIFIC)**  
138, Robinson Road  
The corporate office #14-06  
068906 Singapore  
Tel +65 6323 4131  
Fax +65 6323 4212

**MARM-UPS Pty Ltd. (AUSTRALIA)**  
Unit 22/80 Box Road  
Taren Point NSW 2229  
Tel +61 2 9531 1999  
Fax +61 2 9531 1988

Unit 17/810-818 Princes Hwy  
Springvale VIC 3171  
Tel +61 3 9574 6922  
Fax +61 3 9574 6933

PO Box 2251  
Yokine South WA 6060  
Tel +61 1300 138,709

Follow us on Social Networks



www.ups-riello.com